

Blow gun

die-cast aluminium nickel-plated

EASY

Art. No. 114323

Type No. 22 K



Exemplary illustration

Standard type.

For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

Technical data

| | |
|-------------------------|---|
| Temperature range | -10 to 50 °C |
| Working pressure | 2 - 6 bar |
| Max. operating pressure | 10 bar |
| Nozzle | M12x1.25 |
| Nozzle type | standard nozzle, bore 1.5 mm |
| Extension | M12x1.25 |
| Material | nickel-plated die-cast aluminium |
| Material push pin | steel 2Cr13 |
| Type of connection | push-in plug for DN 7.2 - 7.8 couplings |
| Connecting thread | G 1/4 |
| Air consumption | 250 l/min at 6 bar |

Commercial data

| | |
|-------------------------|--------------------|
| Customs tariff number | 84242000 |
| Country of origin | CN |
| eCl@ss 5.1.4 | 21060801 |
| eCl@ss 9.0 | 21060801 |
| UNSPSC_Code_v190501 | 27131502 |
| UNSPSC_CodeDesc_v190501 | Compressed air gun |

Material informations

| | |
|----------------------------|-------------------------|
| REACH SVHC1 substance name | lead |
| CAS no. SVHC 1 | 7439-92-1 |
| RoHS materials notice | RoHS compliant |
| REACH Info | contains SVHC substance |

Accessories

| | Art. No. | Type No. |
|---|----------|----------|
| Blow gun holder for aluminium and plastic blow guns, incl. 2 brackets for 90°- or 45°- fixation, incl. screws | 142249 | BPH-1 |
| Thread adapter, Aluminium, ET M12x1.25, IT G 1/4, Length 26 mm | 133178 | 22.14 |

Spareparts

| | Art. No. | Type No. |
|--|----------|----------|
| Standard nozzle, Hole Ø 1.5 mm, Connection M12x1,25, for all air guns made of aluminium / nickel-plated die-cast aluminium | 114344 | 105/5 |