

Handheld tyre gauge

MAX

Art. No. 114520

Type No. 37.014



Exemplary illustration

These pressure gauges are effectively protected against shock and impact by means of a free-standing plastic cap. They can be loaded against gauge pressure and up to the maximum scale value.
With push-in plug for DN 7.2 coupling.

Discontinued product. No longer available. New product 205569 (37.013.2)

Technical data

Version	with twin hold-on connector
Measuring range	0 to 12 bar
Measuring range	0 - 170 psi
Description	uncalibrated
Hose connection	G 1/4, swivelling
Hose length	50 cm

Commercial data

Customs tariff number	90262080
Country of origin	DE
eCl@ss 5.1.4	27200610
eCl@ss 9.0	27200610
UNSPSC_Code_v190501	41103311
UNSPSC_CodeDesc_v190501	Manometers

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Product informations

Single-lever operation: Inflation, deflation and checking with a single handle

To check: lever in home position

To deflate: lever actuated half-way

To inflate: lever fully actuated

Pressure gauge: Ø 80 mm, horizontal operating position, overpressure-proof up to 16 bar, PE protective cap

Operating temperature: -10 to 60 °C

Lever plug and double-sided service station plug: For all tire valves with valve thread VG 8 (cars, trucks, motorcycles), in offset design, especially for dual tires and motorcycles

Also suitable for tire gas (nitrogen)

Spareparts

	Art. No.	Type No.
Hose with garage connector, length 50 cm, G 1/4 swivelling	114536	37.250
Pressure gauge 0 - 12 bar/170 psi 80 mm Ø, for plugging	114541	36.42