


Throttle valve

adjustable with slotted-head screwdriver

PLUS

Art. No. 116845 Type No. 344.018-6-D



Exemplary illustration

For throttling flow rates and regulating the piston speed of cylinders. Small dimensions, ideal for tight spaces. To be screwed directly into the valve or cylinder. The set flow rate can be locked via the lock nut in the version with knurled screw. The variants in banjo bolt construction can be rotated during assembly and are fixed after tightening. The variants with plug-in connector, rotated can also be rotated freely after assembly. The seals and lubricants used are silicone-free.

Technical data

0.401
0 - 10 bar
-20 to 80 °C
Nickel-plated brass
NBR
Yes
Both directions throttling (B)
Plug-in connector
rotating
G 1/8
6 mm
9 mm
31.8 mm
22.5 mm



Commercial data


Customs tariff number	84812090
Country of origin	IT
eCl@ss 5.1.4	27292202
eCl@ss 9.0	27292202
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Markings for valve functions

Both directions throttling



Marking (alphabetical code)

В