

# Stopper

Stainless steel 1.4408

## STAINLESS STEEL

Art. No. 118354

Type No. VSTR12ES4408VK



Exemplary illustration

## Technical data

|                       |                     |
|-----------------------|---------------------|
| Max. working pressure | 20 bar              |
| Thread                | R 1/2               |
| L1                    | 18.5 mm             |
| a/f                   | 10 mm               |
| Thread form           | tapered male thread |
| Standard thread       | DIN EN ISO 7-1      |
| Version               | Square              |

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).


## Commercial data

|                         |                           |
|-------------------------|---------------------------|
| Customs tariff number   | 73072910                  |
| Country of origin       | CN                        |
| eCl@ss 5.1.4            | 22360608                  |
| eCl@ss 9.0              | 22560208                  |
| UNSPSC_Code_v190501     | 40173507                  |
| UNSPSC_CodeDesc_v190501 | Stainless steel pipe plug |

## Material informations

|                            |                            |
|----------------------------|----------------------------|
| REACH SVHC1 substance name | no                         |
| CAS no. SVHC 1             | no CAS No.                 |
| RoHS materials notice      | RoHS compliant             |
| REACH Info                 | no SVHC substance included |

## Dimensions



| Thread | L1<br>mm | a/f<br>mm |
|--------|----------|-----------|
| R 1/2  | 18.5     | 10        |

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).