

Removable double threaded nipple

Stainless steel 1.4408

STAINLESS STEEL

Art. No. 118872

Type No. LDGNG112ES4408FDIA



Exemplary illustration

Technical data

Max. working pressure	20 bar
Sealant	Flat sealing PTFE
Thread	G 1 1/2
L1	80.0 mm
a/f 1	72 mm
a/f 2	54 mm
Thread form	parallel female thread and male thread
Standard thread	DIN EN ISO 228-1

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).


Commercial data

Customs tariff number	73072910
Country of origin	CN
eCl@ss 5.1.4	22360606
eCl@ss 9.0	22560206
UNSPSC_Code_v190501	40173303
UNSPSC_CodeDesc_v190501	Stainless steel pipe nipple

Material informations

REACH SVHC1 substance name	no
CAS no. SVHC 1	no CAS No.
RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

Dimensions



Thread	L1 mm	a/f 1 mm	a/f 2 mm
G 1 1/2	80.0	72	54

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).

Spareparts

	Art. No.	Type No.
Flat seal made of PTFE size 7	119509	FDT7