

# Hexagonal counter nut

Stainless steel 1.4408

## STAINLESS STEEL

Art. No. 119336

Type No. SKMG34ES4408



Exemplary illustration

## Technical data

Max. working pressure	20 bar
Thread	G 3/4
a/f	36 mm
Thread form	parallel female thread
Standard thread	DIN EN ISO 228-1

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).


## Commercial data

Customs tariff number	73072910
Country of origin	CN
eCl@ss 5.1.4	27299290
eCl@ss 9.0	27299290
UNSPSC_Code_v190501	40141616
UNSPSC_CodeDesc_v190501	Valve parts or accessories

## Material informations

REACH SVHC1 substance name	no
CAS no. SVHC 1	no CAS No.
RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

## Dimensions



Thread	a/f mm	A mm
G 3/4	36	9.0

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).