


# Stainless steel pressure regulator

made of stainless steel 1.4404

Art. No. 136419

Type No. DRES.G34R.1-17B.T



Exemplary illustration

Stainless steel regulators with secondary venting (reversible) for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc.  
Pressure setting by hexagon head screw.

## Technical data

Max. input pressure	60 bar
Min. medium temperature	-40 °C
Max. medium temperature	80 °C
Min. ambient temperature	-40 °C
Max. ambient temperature	80 °C
Control range	1 - 17 bar
Housing	Stainless steel 1.4404 (AISI 316L)
Sealant	PU/HNBR
Diaphragms	HNBR
Flow rate	3500 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p \leq 1$ bar
Thread	G 3/4
A	179.0 mm
B	68.0 mm
C	47.0 mm
D	3/4
E	68.0 mm
F	47.0 mm
G	22.0 mm
H	32.0 mm
I	36.0 mm


Possible certificate types according to DIN EN 10204 (available at an extra charge): 3.1 Material acceptance test certificate with details of the batch used

MOCA (1935/2004/EU) certified devices available on request

## Commercial data

Customs tariff number	84811019
Country of origin	IT
eCl@ss 5.1.4	37011108
eCl@ss 9.0	37011108
UNSPSC_Code_v190501	41112404
UNSPSC_CodeDesc_v190501	Pressure regulator

## Dimensions



## Accessories

	Art. No.	Type No.
Mounting bracket, for pressure, filter regulator and filter, G 1/2 and G 3/4	135520	HWDRFRFES.G12.G34.T

## Spareparts

	Art. No.	Type No.
Wear part set, for pressure and filter regulator, G 1/2 and G 3/4	134983	VTSDRFRES.G12.G34R.T
Pressure gauge Ø 63 mm, G 1/4 ET, 0 - 25 bar	102511	4086