


Straight push-in fitting

»metallica« series

PLUS ||

Art. No. 136775

Type No. 846.012-16



Exemplary illustration

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Technical data

Working pressure	-0.98 -16 bar
Operating temperature	-20 to 150 °C
Series	metallica
Material	nickel-plated brass
Medium	compressed air
Sealant	FKM
Sleeve	Nickel-plated brass
Clamping ring	Stainless steel
Applications	Compressed air systems, welding technology, vacuum
Recommended hose	PA, PU
Thread form	parallel female thread
Thread	G 1/2 IT
for tube O.D.	16 mm
L1	41.0 mm
a/f	24 mm
Outer hex	with


Commercial data

Customs tariff number	74122000
Country of origin	IT
eCl@ss 5.1.4	27294201
eCl@ss 9.0	27294201
UNSPSC_Code_v190501	27131613
UNSPSC_CodeDesc_v190501	Air coupling

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

Dimensions



Thread	for tube O.D.	Ø B	Ø C	H	a/f	L1
	mm	mm	mm	mm	mm	mm
G 1/2 IT	16	24,0	14.5	15.0	24	41.0