

Activated carbon filters

PLUS

Art. No. 146959

Type No. FSPA.G2



Exemplary illustration

For adsorbing vaporous media.

A micro-filter must be connected upstream if dried air is not available.

Technical data

Input pressure	4 - 16 bar
Temperature range	5 to 50 °C
Housing	aluminium
filter bowl	aluminium
Residual oil content	0.003 mg/m ³
Filter element	activated carbon
End caps	plastic
Support sleeves	stainless steel SS310
Indicating range of differential pressure gauge	0 - 1 bar
Flow rate measurement	at P ₁ = 7 bar and pressure drop Δ _p = 0.1 bar
Thread	G 2
Flow rate	15670 l/min
A	162.0 mm
C	55.0 mm
D	648.0 mm
Version	with differential pressure gauge
Condensate drain	semi-automatic bleeder valve
Recommended change intervals	every 4000 operating hours, after 6 months at the latest (filter element), once a year (bleeder valve)

Commercial data

Customs tariff number	84213925
Country of origin	MY
eCl@ss 5.1.4	27293004
eCl@ss 9.0	27293004
UNSPSC_Code_v190501	40161505
UNSPSC_CodeDesc_v190501	Air filters

Spareparts

	Art. No.	Type No.
Differential pressure gauge, pre-, micro-, active charcoal filter	146967	FSPDM.0-1B
Semi-automatic bleeder valve, G 2	147710	HAAFSPVM.G2
Filter element, G 2	147731	FEFSPA.G2