


Constant pressure regulator

EASY

Art. No. 147527

Type No. DRK.G114.BG5.0,5-25B



keine Abb. vorhanden

Exemplary illustration

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.
The pressure regulators maintain a constant working pressure regardless of variations in the inlet pressure.

Technical data

Medium temperature	-10 to 60 °C
Ambient temperature	-10 to 60 °C
Sealant	NBR
Spring bonnet	brass
Flow rate measurement	at $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Thread	G 1 1/4
Size	5
Max. input pressure	40 bar
Housing	die-cast aluminium
Control range	0,5 - 25 bar
Flow rate	19000 l/min
A	125.0 mm
B	218.0 mm
C	52.0 mm
D	166.0 mm
E	119.0 mm

Commercial data

Customs tariff number	84811099
Country of origin	DE
eCl@ss 5.1.4	37011108
eCl@ss 9.0	37011108
UNSPSC_Code_v190501	41112453
UNSPSC_CodeDesc_v190501	Pressure regulator

Spareparts

	Art. No.	Type No.
Wear part set for constant pressure regulator, size 5, suitable for control range max. 25 bar	147541	VTSDRK.BG5.25B
Standard pressure gauge, Single scale bar, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0 - 40 bar, Ø 63	101757	220-K