

2/2-way solenoid valve

2/2-way type

Art. No. 148587

Type No. MVB.ES.230V.G12.0,5-12B



Exemplary illustration

The standard series in the versions

- directly operated
- pilot operated

Cable plug in acc. with ISO 4400

Medium temperature max. 130 °C

Technical data

Housing	Stainless steel 1.4401
Valve seat	Stainless steel
Internal parts	Stainless steel
Protection IP	IP 65
Type	4
Thread	G 1/2 IT
Operating pressure	0.5 - 12 bar
Sealant	EPDM
Electrical connection	ISO 4400 / EN 175301-803 industrial standard type A
Medium temperature	-10 to 130 °C
Ambient temperature	-10 to 60 °C
Standard thread	ISO 228-1
Opening	12.5 mm
A	82.0 mm
B	79.0 mm
C	52.0 mm

Commercial data

Customs tariff number	84812090
Country of origin	TR
eCl@ss 5.1.4	27220601
eCl@ss 9.0	27220601
UNSPSC_Code_v190501	40141605
UNSPSC_CodeDesc_v190501	Solenoid valves

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

