

# Spiral hose coupling set

Spiral hose polyurethane

**MAX** ||

Art. No. 158185

Type No. SP121000PUSK



Exemplary illustration

These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional polyamide spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

## Technical data


Operating temperature	-20 to 60 °C
Max. operating pressure at 23 °C	10 bar
Hose size	12x8 mm
No. of coils	54
Service length max.	10.0 m
Coil O.D.	82 mm
Material	Polyester polyurethane
Shore hardness	98A

with quick disconnect coupling DN 7.2 and push-in plug, bare brass

## Commercial data

Customs tariff number	39173300
Country of origin	CN
eCl@ss 5.1.4	27294101
eCl@ss 9.0	27294190
UNSPSC_Code_v190501	40142002
UNSPSC_CodeDesc_v190501	Air hoses

## Service length



The service length is the maximum permissible extension (limit value).  
After exceeding the limit value, a permanent deformation can occur.

## Spareparts

	Art. No.	Type No.
Spiral hose, Fitting, Kink protection spring, PU, Hose Ø12x8, 10m	158167	SP121000PU
Quick-connect coupling I.D. 7.2 »connect line«, G 3/8 IT	115632	243.22-E
Nipple for couplings I.D. 7.2 - 7.8, bright brass, G 3/8 IT	107243	243.56