



Elbows

Stainless steel 1.4408


Max. operating pressure max. 20 bar
Max. operating temperature max. 175 °C



253.13-ES

90° elbow, female-female, Rp thread acc. to ISO 7-1


| Art. No. | Type No. | Thread | A mm | B mm |
|----------|-----------|--------|------|------|
| 112666 | 253.11-ES | Rp 1/8 | 16.4 | 16.4 |
| 112667 | 253.12-ES | Rp 1/4 | 19.2 | 20.0 |
| 112668 | 253.13-ES | Rp 3/8 | 22.5 | 23.5 |
| 112669 | 253.21-ES | Rp 1/2 | 27.4 | 27.4 |
| 112670 | 253.22-ES | Rp 3/4 | 31.1 | 32.2 |
| 112671 | 253.23-ES | Rp 1 | 36.9 | 40.0 |



253.46-ES

45° elbow, female-female, Rp thread acc. to ISO 7-1


| Art. No. | Type No. | Thread | L mm | Ø mm |
|----------|-----------|--------|------|------|
| 112672 | 253.41-ES | Rp 1/8 | 15.6 | 16.5 |
| 112673 | 253.42-ES | Rp 1/4 | 15.9 | 19.9 |
| 112674 | 253.43-ES | Rp 3/8 | 17.6 | 23.5 |
| 112675 | 253.44-ES | Rp 1/2 | 19.2 | 27.6 |
| 112676 | 253.45-ES | Rp 3/4 | 22.8 | 32.5 |
| 112677 | 253.46-ES | Rp 1 | 26.7 | 40.0 |



253.18-ES

90° elbow, female-male, female thread: Rp thread acc. to ISO 7-1, male thread: R thread acc. to ISO 7-1



| Art. No. | Type No. | Female Thread | Male Thread | H mm | L mm |
|----------|-----------|---------------|-------------|------|------|
| 112678 | 253.15-ES | Rp 1/8 | R 1/8 | 17.0 | 24.0 |
| 112679 | 253.16-ES | Rp 1/4 | R 1/4 | 20.0 | 28.0 |
| 112680 | 253.17-ES | Rp 3/8 | R 3/8 | 22.0 | 32.0 |
| 112681 | 253.18-ES | Rp 1/2 | R 1/2 | 27.0 | 38.0 |
| 112682 | 253.19-ES | Rp 3/4 | R 3/4 | 32.0 | 45.0 |
| 112683 | 253.20-ES | Rp 1 | R 1 | 37.0 | 52.0 |



253.66-ES

X-distributor, 4 x female, Rp thread acc. to ISO 7-1

| Art. No. | Type No. | Thread | A mm |
|----------|-----------|--------|------|
| 112684 | 253.61-ES | Rp 1/8 | 19.0 |
| 112685 | 253.62-ES | Rp 1/4 | 19.0 |
| 112686 | 253.63-ES | Rp 3/8 | 23.0 |
| 112687 | 253.64-ES | Rp 1/2 | 27.0 |
| 112688 | 253.65-ES | Rp 3/4 | 32.0 |
| 112689 | 253.66-ES | Rp 1 | 38.0 |



254.36-ES

Tee distributor, 3 x female, Rp thread acc. To ISO 7-1

| Art. No. | Type No. | Thread | L mm | A mm |
|----------|-----------|--------|------|------|
| 112690 | 254.33-ES | Rp 1/8 | 34.0 | 17.0 |
| 112691 | 254.34-ES | Rp 1/4 | 38.0 | 19.0 |
| 112692 | 254.35-ES | Rp 3/8 | 46.1 | 22.0 |
| 112693 | 254.36-ES | Rp 1/2 | 54.0 | 27.0 |
| 112694 | 254.37-ES | Rp 3/4 | 63.0 | 32.0 |
| 112695 | 254.38-ES | Rp 1 | 73.0 | 36.0 |